


Product Information lisocore® Sliding door panel

Panel composition:

| | |
|------------------|---|
| Panel thickness: | 40,0 mm |
| Size: | 2.800 x 2.070 mm |
| Inlays: | 2 pieces 95,0 x 2.070 mm Birch-Multiplex |
| Weight: | 80 kg / Panel \approx 13,8 kg/m ² (at above mentioned size) |
| Cover layer: | 8,0 mm MDF |
| Coating: | lisocore® RECOAT Melamine K0101 SM |



The matt lisocore® RECOAT surface is ideally suited for the material-saving application of a primer or varnish – after just one sanding process for cleaning!



The patented structure guarantees a very high bending strength as well as low self-weight!

Multiplex-Inlays on both sides are the basis for all fastening systems designed for highest demands.

Product Information

lisocore® Sliding door panel

Application example:


Sliding doors for wardrobes

Data single sliding door:

- Cutted size: 2500 x 1300 x 40 mm
- Weight: 48 kg
- Without edge bending or handle-strip

When used as a wardrobe sliding door in the shown installation situation, there is a deflection of < 4 mm over the length of the door after a period of 30 days.

Installation situation:



Just do it!

Christian Herdemerten shows in his video, how simple and fast it is to build a sliding door out of **lisocore®**!

We are very happy to assist you with any questions!

Please get in touch with your contact person or:

verkauf@pyrus-panels.com
+49 8061/34979-0

lisocore®

The sustainable High-Performance Board!