



Ultra Ply LLC Industrial ave, 27B/4-3
Smorgon, Belarus, 231000
Tel: +375159241219, Fax: 0375159241227
www.kronospan.com.by

Declaration of Constant Performance according to
the Regulation EU No. 305/2011 (CPR)
No. DoP-SM21-01-2020/01/13

DECLARATION OF PERFORMANCE No. DoP-SM21-01-2020/01/13

1. Product identification code:

Plywood uncoated and not treated from thick pine veneers with the thickness 9-40 mm

2. Intended purpose of the product:

Plywood for use as structural components in humid conditions, application class EN 636 – 2 S

3. Name and contact address of the manufacturer:

**Ultra Ply LLC
Industrial ave, 27B/4-3
Smorgon, Belarus, 231000**

4. Name and address of authorized representative: not applicable

5. System for evaluating and monitoring the consistency of performance:

AVCP System 2+

6. Harmonized standard:

EN 13986:2004+A1:2015

7. Authorized certification body for production control at the factory:

The authorized certification body of MPA Eberswalde carried out an primary inspection of the company and also carried out production and continuous monitoring, evaluation and control according to the CE System 2+ as described in the harmonized standard EN 13986:2004+A1:2015. In addition, it carried out a study of samples taken from the factory in accordance with the established schedule in the CE System 2+ and issued a Certificate of Conformity of the Factory Production Control to System 2+; No. 0763 - CPR 6090.

8. Declared properties:

Essential characteristics	Value	Harmonized standard
Bonding quality	Class 2	EN 636:2012+A1:2015
Durability (Moisture resistance)	use in humid conditions	EN 13986:2004+A1:2015
Formaldehyde emission	Class E1	
Reaction to fire	NPD	EN 13986:2004+A1:2015



Ultra Ply LLC Industrial ave, 27B/4-3
Smorgon, Belarus, 231000
Tel: +375159241219, Fax: 0375159241227
www.kronospan.com.by

Declaration of Constant Performance according to
the Regulation EU No. 305/2011 (CPR)
No. DoP-SM21-01-2020/01/13

Water vapor permeability	NPD	EN 13986:2004+A1:2015
Airborne sound insulation	NPD	
Sound absorption	NPD	
Thermal conductivity	NPD	
Strength and stiffness for structural use	NPD	
Mechanical durability	NPD	
Biological durability	NPD	
Pentachlorophenol (PCP) content	≤5 ppm	
Racking resistance	NPD	
Embedment strength	NPD	

Nominal thickness	9	12	15	18	21	24	27	30	33	39	Harmonized standard
Index	Value										EN 13986:2004+A1:2015
Bending strength class F to EN 636											
f_{II}	30	20	20	35	30	30	30	25	25	20	
f_B	10	10	10	15	15	15	20	20	15	15	
Elastic strength (elastic modulus) class E to EN636											
E II	80	60	70	70	70	70	70	60	60	60	
E_B	5	15	15	20	30	30	40	35	35	35	

Properties of the product specified above according to the statements accepted. This property declaration is issued in accordance to EU Regulation No. 305/2011, on the responsibility of the manufacturer specified above.

These declared performance characteristics are the sole responsibility of the manufacturer referred to in paragraph 3.

Signed for and on behalf of the manufacturer:

 Salat Zdenek, Director

«Ultra Ply» LLC, Smorgon, Belarus 13.01.2020